

## SS0110 32.768kHz Crystal Oscillator

**TECHNOLOGY: 180nm SMIC G**  
**Status: under development**

### KEY FEATURES

- large supply voltage range: 0.9 – 2V
- ultra low-power
- output frequency 32.768 kHz
- internal bias resistor
- internal AGC (ultra low-power and high frequency precision)
- internal shunt capacitors (optional)

### SHORT DESCRIPTION

SS0110 is a pierce oscillator for 32.768kHz crystals. The oscillator is specifically designed ultra low-power applications. The large supply voltage range makes SS0110 the optimal choice for ASICs powered by a low-capacity battery (e.g. paper battery) or a supercapacitor. The internal AGC guarantees the minimum power consumption over process, temperature and supply corner space, whichever 32Hz crystal is selected. Furthermore, AGC limit signal distortion and avoids quartz stress, thus providing high frequency precision and low aging.

### APPLICATIONS

RTC, timers; battery or supercap supply.

### PIN FUNCTIONS

#	NAME	DESCRIPTION	NOTE
1	GND	Ground	
2	XIN	Crystal Input	
3	XOUT	Crystal Output	
4	EN	Negative Enable	
5	VDD	Power Supply	

### OPERATING CONDITIONS

Symbol	Parameter	Min	Max	Unit
VDD	Supply voltage	1	2	V
T	Storage temperature	-40	85	°C
ESD	ESD protection level, HBM		2	kV

### RECOMMENDED CRYSTAL SPECIFICATION (32 kHz)

Symbol	Parameter	Min	Max	Unit
ESR	Effective Series Resistance		80	kΩ
CL	Load Capacitance	8	12.5	pF

### ELECTRICAL CHARACTERISTICS

Conditions: VDD from 1 to 2V, T from -40 to +85°C, EN=0, unless otherwise stated.

Parameter	Condition	Min	Typ	Max	Unit	Note
-----------	-----------	-----	-----	-----	------	------

Current Consumption	IDD			450		nA	
Stand-by Current	IDDZ	EN=VDD				nA	
Start-Up from Enable	tstart1					ms	
Start-Up from VDD	tstart1	Note 1			1.5	s	
Output frequency	fout	Note 2		32		KHz	
High-level output voltage	VOH			VDD			
Low-level output voltage	VOL			0			
Rise and fall time	tr/tf	Evaluated at 20% - 80% levels		2.5		nS	
Output duty cycle	DUC			55%			
Peak-to-peak voltage across crystal	Vppxtal			250		mV	

note 1	VDD ramp-up from 0 to final value. Typical VDD rise time: XX
note 2	Frequency nominal value and accuracy depends on the external quartz

#### NOTICE

Silis srl (Silis) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time. Customers should obtain the latest information before submitting orders and should verify that such information is current and complete.

Silis assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using Silis components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

Reproduction of Silis information in Silis data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Silis is not responsible or liable for altered documentation.

Silis products are not authorized for use in safety-critical applications (such as life support) where a failure of the Silis product would reasonably be expected to cause severe personal injury or death, unless officers of the parties have executed an agreement specifically governing such use.